

**Rope light** - manufactured according to EN 60598-1 and EN 60598-2-21 standards. 220-240volt~, 50Hz, AC

The melting point of PVC is 105 °C.



**CE IP44**



## Technical data

Item:	Length/section	Lamps/1m	Watt/1m	Max length/watt
563-10/11/12/13/14	1m	60	8W	40m/320W

220-240V AC 50 Hz

Model No.: TY-SMD-R1-30M

### Important!

- Do not connect the rope light to the mains while it is still in the packaging or rolled up on the bobbin.
- We recommend that this product be installed by an authorised electrician. National regulations must be followed.
- The rope light must always be properly fused.
- All technical questions should be referred to an authorised electrician.
- We recommend using an earth leakage circuit breaker for the 220-240V light.
- Do not use the rope light covered or recessed into a surface.
- Do not connect the rope light to any other manufacturer's product.
- The light can only be connected to Star Trading's connecting parts.
- Any open ends must be sealed before use.

### Instructions:

Cutting to length:

The rope light can only be cut at the markings shown using a sharp pair of end cutting nippers. Ensure that the cut is vertical with no frayed edges.

Connecting and connecting parts:

Use only StarTrading's connecting cable and components. See the instructions shipped with the cable and components.

Save this documentation for future reference as it contains vital safety information.

**STAR**<sup>®</sup>  
TRADING  
STAR STREET 1  
512 50 SVENJUNGA  
SWEDEN  
[www.startrading.com](http://www.startrading.com)